

### Stormwater Minimum Requirements Checklist

Community Development Department \* 80 Columbia Avenue \* Marysville, WA 98270 (360) 363 -8100 \* (360) 651-5099 FAX \* Office Hours: Monday - Friday 7:30 AM -4:00 PM

#### **Instructions**

Please complete this form to document which stormwater minimum requirements apply to your project and how minimum requirement 5 will be addressed (when applicable). The City has adopted the Washington State Department of Ecology 2012 Stormwater Management Manual for Western Washington as amended in December 2014 (Stormwater Manual). The minimum requirements thresholds can be found in MMC 14.15.040 and 14.15.050. Refer to the Stormwater Manual for minimum requirement details. Return with all other required information the Engineering Services Manager of the Community Development Department. For an online form go to <a href="http://www.marysvillewa.gov/101/Engineering-Services">http://www.marysvillewa.gov/101/Engineering-Services</a>

### Section 1: Which minimum requirements apply to your project?

Project Name:	City File #:	
No minimum requirements apply	Stop here	
Minimum Requirement 2	Stop here	
Minimum Requirements 1-5	Complete Section 2, below	
Minimum Requirements 1-9	Skip to Section 3, page 3	

### Section 2: Projects triggering only Minimum Requirements #1 through #5

$\square$ Low Impact Development Performance Standard and BMP T5.13; or		
□ List # 1		

If using list #1, consider the BMP's in the order listed for each type of surface. Use the first BMP that is considered feasible. No other On-site Stormwater Management BMP is necessary for the surface to meet minimum requirement 5. Feasibility shall be determined by evaluation against:

- 1. Design criteria, limitations, and infeasibility criteria identified for each BMP in the Stormwater Manual; and
- 2. Competing Needs Criteria listed in <a href="Chapter V-5 On-Site Stormwater Management">Chapter V-5 On-Site Stormwater Management</a>.

Record which BMPs are feasible or infeasible below. For infeasible BMP's cite the reason for infeasibility, and/or a reference to the supporting documentation (for example the page number in a geotechnical report).

# List #1: On-site Stormwater Management BMPs for Projects Triggering Minimum Requirements #1 through #5

Lawn and landscaped areas						
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.			
BMP T5.13: Post-Construction Soil Quality and Depth						
Roofs						
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.			
BMP T5.30: Full Dispersion or BMP T5.10A: Downspout Full Infiltration						
BMP T5.14A: Rain Gardens or BMP T7.30: Bioretention Cells, Swales, and Planter Boxes *						
BMP T5.10B: Downspout Dispersion Systems						
BMP T5.10C: Perforated Stub-out Connections						
Other Hard Surfaces						
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.			
BMP T5.30: Full Dispersion						
BMP T5.15: Permeable Pavements, or BMP T5.14A: Rain Gardens, or						
BMP T7.30: Bioretention Cells, Swales, and Planter Boxes*						
BMP T5.12: Sheet Flow Dispersion, or BMP T5.11: Concentrated Flow Dispersion						
For Residential Developments Only						
$\square$ Provide a typical lot layout showing where the feasible BMP's, as determined above, will be placed on the lots						

<sup>\*</sup> The rain garden or bioretention facility must have a minimum horizontal projected surface area below the overflow which is at least 5% of the area draining to it.

### Section 3: Projects triggering Minimum Requirements #1 through #9

☐ Low Impact Development Performance Standard and BMP T5.13; or	
☐ List # 2	

For each surface, consider the BMPs in the order listed for that type of surface. Use the first BMP that is considered feasible. No other On-site Stormwater Management BMP is necessary for that surface to fulfill Minimum Requirement #5. Feasibility shall be determined by evaluation against:

- 1. Design criteria, limitations, and infeasibility criteria identified for each BMP in the Stormwater Manual; and
- 2. Competing Needs Criteria listed in <u>Chapter V-5 On-Site Stormwater Management</u>.

### List #2: On-site Stormwater Management BMPs

Lawn & Landscaped Areas				
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.	
BMP T5.13: Post-Construction Soil Quality and Depth				
		Roofs		
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.	
BMP T5.30: Full Dispersion, or BMP T5.10A: Downspout Full Infiltration				
BMP T7.30: Bioretention Cells, Swales, and Planter Boxes*				
BMP T5.10B Downspout Dispersion Systems				
BMP T5.10C: Perforated Stub-out Connections				
Other Hard Surfaces				
	Feasible	Infeasible	type reason here and/or add reference to a pg. # in a supporting doc.	
BMP T5.30: Full Dispersion				
BMP T5.15: Permeable Pavements				
BMP T7.30: Bioretention Cells, Swales, and Planter Boxes*				
BMP T5.12: Sheet Flow Dispersion, or BMP T5.11: Concentrated Flow Dispersion				
For Residential Developments Only				
☐ Provide a typical lot layout showing where the feasible BMP's, as determined above, will be placed				
on the lots				

\* The facility must have a minimum horizontal projected surface area below the overflow which is at least 5% of the area draining to it.

## **Section 4: Contact information**

Project Engineer:	
Address:	
Phone:	E-Mail:
Signature:	